H_1xHDMI2.0+1xDP1.2 input card	 **Only one connector can be used each time**. Set to use which connector on the Web page. The default option is HDMI 2.0 connector. Support for embedded audio and 144Hz input Does not support interlaced signal input. ● 1x HDMI 2.0 – Backward compatible with HDMI 1.4 and HDMI 1.3 – Supports the maximum resolution of 3840×2160@60Hz and the minimum resolution of 800×600@59.94Hz. – HDCP 2.2 compliant – Custom resolutions: Max. width: 4092 pixels (4092×2263@60Hz) Max. height: 4095 pixels (2188×4095@60Hz) ● 1x DP 1.2 – Backward compatible with DP 1.1 – Supports the maximum resolution of 4096×2160@60Hz or 8192×1080@60Hz and the minimum resolution of 800×600@59.94Hz. – HDCP 2.2 compliant – Custom resolutions: Max. width: 8192 pixels (8192×1152@60Hz) Max. height: 4095 pixels (2188×4095@60Hz) Status LEDs: ● On: The input source is accessed normally. ● Off: No input source is accessed or the input source is abnormal. Specifications: ● Weight: 550 g ● Dimensions: 193 mm × 247.12 mm × 21.15 mm ● Power consumption: 9.6 W