Lilliput

Q24 23.6 inch 12G-SDI professional broadcast production studio monitor

SKU:
Q24
Screen Size:
23.6 inches
Resolution:
3840x2160
Housing Material:
Metal
Brightness:
300 cd/m^2
Inputs:
12G-SDI*2, 3G-SDI*2, HDMI 2.0, 12G SFP

Screen Size

Screen Size 23.6 inches

Resolution 3840x2160

Housing Material Metal

Brightness 300 cd/m^2

Inputs 12G-SDI*2, 3G-SDI*2, HDMI 2.0, 12G SFP

Product Description

DISPLAY	Panel	23.6″
	Physical Resolution	3840*2160
	Aspect Ratio	16:09
	Brightness	300 cd/m²
	Contrast	1000：1
	Viewing Angle	178°/178°（H/V）
	HDR	ST2084 300/1000/10000/HLG
	Supported Log Formats	SLog2 / SLog3 / CLog / NLog / ArriLog / JLog or User…
	Look up Table(LUT)support	3D LUT (.cube format)
	Technology	Calibration to Rec.709 with optional calibration unit
VIDEO INPUT	SDI	2×12G, 2×3G (Supported 4K-SDI Formats Single/Dual/Quad Link)
	SFP	1×12G SFP+(Fiber module for optional)
	HDMI	1×HDMI 2.0
VIDEO LOOP OUTPUT	SDI	2×12G, 2×3G (Supported 4K-SDI Formats Single/Dual/Quad Link)
	HDMI	1×HDMI 2.0
SUPPORTED FORMATS	SDI	2160p 24/25/30/50/60, 1080p 24/25/30/50/60, 1080pSF 24/25/30, 1080i 50/60…
	SFP	2160p 24/25/30/50/60, 1080p 24/25/30/50/60, 1080pSF 24/25/30, 1080i 50/60…
	HDMI	2160p 24/25/30/50/60, 1080p 24/25/30/50/60, 1080i 50/60, 720p 50/60..
AUDIO IN/OUT (48kHz PCM AUDIO)	SDI	16ch 48kHz 24-bit
	HDMI	8ch 24-bit
	Ear Jack	3.5mm
	Built-in Speakers	2
	RS422	In/out
REMOTE CONTROL	GPI	1
	LAN	1
POWER	Input Voltage	DC 12-24V
	Power Consumption	≤55W (15V)
	Compatible Batteries	V-Lock or Anton Bauer Mount
	Input Voltage(battery)	14.8V nominal
ENVIRONMENT	Operating Temperature	0℃~40℃
	Storage Temperature	-20℃~60℃
OTHER	Dimension(LWD)	567mm × 376.4mm × 45.7mm
	Weight	7.4kg
DISPLAY	Panel	23.6″
	Physical Resolution	3840*2160
	Aspect Ratio	16:09
	Brightness	300 cd/m²

	Contrast	1000：1
	Viewing Angle	178°/178°（H/V）
	HDR	ST2084 300/1000/10000/HLG
	Supported Log Formats	SLog2 / SLog3 / CLog / NLog / ArriLog / JLog or User…
	Look up Table(LUT)support	3D LUT (.cube format)
	Technology	Calibration to Rec.709 with optional calibration unit
VIDEO INPUT	SDI	2×12G, 2×3G (Supported 4K-SDI Formats Single/Dual/Quad Link)
	SFP	1×12G SFP+(Fiber module for optional)
	HDMI	1×HDMI 2.0
VIDEO LOOP OUTPUT	SDI	2×12G, 2×3G (Supported 4K-SDI Formats Single/Dual/Quad Link)
	HDMI	1×HDMI 2.0
SUPPORTED FORMATS	SDI	2160p 24/25/30/50/60, 1080p 24/25/30/50/60, 1080pSF 24/25/30, 1080i 50/60…
	SFP	2160p 24/25/30/50/60, 1080p 24/25/30/50/60, 1080pSF 24/25/30, 1080i 50/60…
	HDMI	2160p 24/25/30/50/60, 1080p 24/25/30/50/60, 1080i 50/60, 720p 50/60..
AUDIO IN/OUT	SDI	16ch 48kHz 24-bit
(48kHz PCM AUDIO)	HDMI	8ch 24-bit
	Ear Jack	3.5mm
	Built-in Speakers	2
	RS422	In/out
REMOTE CONTROL	GPI	1
	LAN	1
POWER	Input Voltage	DC 12-24V
	Power Consumption	≤55W (15V)
	Compatible Batteries	V-Lock or Anton Bauer Mount
	Input Voltage(battery)	14.8V nominal
ENVIRONMENT	Operating Temperature	0℃~40℃
	Storage Temperature	-20℃~60℃
OTHER	Dimension(LWD)	567mm × 376.4mm × 45.7mm
	Weight	7.4kg