LILLIPUT® **15.6" 23.8" 28"** Carry-on 4K Broadcast Director Monitor Series



3840×2160 | 12G-SDI | 4K HDMI

Broadcast monitor for 4K/Full HD camcorder & DSLR
Application for taking photos & making movies


12G-SDI Single-Link

COMPLY WITH STANDARDS

- ST2081-10 1×6G-SDI
- ST2082-10 1×12G-SDI

SDI Compatibility

The BM-150 monitor series support 12G-SDI single-link signal input and loop output, and backward compatible with 6G-SDI, 3G-SDI, HD-SDI input signals.





12G-SDI Dual-Link

COMPLY WITH STANDARDS

- ST2081-11 2×6G-SDI
- ST425-3 2×3G-SDI



3840×2160



SDI Compatibility The BM-150 monitor series support 2×6G-SDI dualink signal input and loop output, and backward compatible with 2xSD-SDI & 2xHD-SDI input signals.

12G-SDI Quad-Link

COMPLY WITH STANDARDS

- ST425-3 4×HD-SDI
- ST425-5 4×3G-SDI

Square Division (4K mode)

Each bin contains a full image at 1/4 resolution.




3840×2160



2 Sample Interleave (4K mode)

Each bin contains a full image at 1/4 resolution.




3840×2160





SDI equalization & re-clocking

The qualities of the eye-waveform is to represent the quality of the SDI signal signal. To the SDI equalizer & re-clocking function, ensures the final cameras, quality and effect of your system.



4K HDMI Signal Inputs

Matches with world-famous 4K/FHD camera brands, to assist cameraman in better photography experience.

4K HDMI Formats

- HDMI 2.0 supports 4K 60Hz signal input.
  4:4:4@2160 (3840×2160)@60Hz(8bits)
  4:2:2@2160 (3840×2160)@60Hz(8bits)
- HDMI 1.4 supports 4K 30Hz signal input.





Multiple Views Display

It supports Quad View with 4x HDMI or 1x SDI (plus4k) 12G/6G/3G...) and 3x HDMI. Also supports Picture-in-Picture function.

Camera Auxiliary Functions

Plenty of auxiliary functions for taking photos and making movies, such as peaking, false color and audio level meter





6U Rack Mounts

Intelligent SDI Monitoring

It has a variety of industry standards for transport, or rate monitoring, and full compliance with the SMPTE standard. Support for 3G-SDI, 6G-SDI, 12G-SDI signals, and has all the answers. A 5.2-inch 3.5 or customized monitoring solution shop. Get the support for views, four different angles and images clearer.





SPECIFICATIONS | ACCESSORIES

		BM150-12G	BM230-12G	BM280-12G
DISPLAY	Panel	15.6" IPS	23.8" IPS	28" 10bit IPS
	Physical Resolution	3840×2160		
	Brightness	300cd/m²	300cd/m²	300cd/m²
	Contrast	1000:1		
	Viewing Angle	178° / 178°	178° / 178°	170° / 160° (H/V)
INPUT	12G-SDI	1		
	3G-SDI	2		
	HDMI	HDMI 2.0×1 (support 4K 60Hz) HDMI 1.4×3 (support 4K 30Hz)		
	DC-IN	1		
OUTPUT	12G-SDI	1		
	3G-SDI	2		
AUDIO	Headphone	1		
	Ear Phone Slot	1		
POWER	Current	2.8A (12V)	4.1A (12V)	4.1A (12V)
	Power Voltage	DC 12-24V (6-30)		
	Battery Plate	V-mount or Anton Bauer mount		
	Power Consumption	≤5W	≤8.5W	≤8.5W
ENVIRONMENT	Operating Temperature	0°C~40°C		
	Storage Temperature	-20°C~60°C		
DIMENSION	Weight	3.4kg / 7.5lg	6.0kg / 13kg/lb	6.4kg / 21kg/with cases

Note: Due to constant effort to improve products and product features, specifications may change without notice.

1. Folding sun shade cover		1 piece
2. Carry-on sunbase		1 piece
3. 15V DC adapter		1 piece
4. Adapter fixing belt		1 piece
5. Battery plate bracket		1 piece
6. V-mount or Anton Bauer mount		1 piece
7. Base bracket		1 pair
8. TALLY connector (in bulk)		1 piece
9. Manual		1 copy
10. Acrylic screen protector	(Applied to BM150-12G)	1 piece

SDI FORMAT UNDER 4K MODE

6G-HD (ST 424-3)	3840x2160/4096x2160 (23.98/24/25/29.97/30p) 3840x2160/4096x2160 (47.95p/48p/50/59.94/60p)
3G-SDI (ST 424-5)	3840x2160/4096x2160 (23.98/24/25/29.97/30p)
2SI-3G (ST 425-5)	3840x2160/4096x2160 (47.95p/48p/50/59.94/60p)
6G-SDI (ST 2081-10)	3840x2160/4096x2160 (23.98/24/25/29.97/30p) 3840x2160/4096x2160 (47.95/48/50/59.94/60p)
12G-SDI (ST 2082-10)	1920x1080/2048x1080 (47.95/48/50/59.94/60p) 3840x2160/4096x2160 (47.95/48/50/59.94/60p) 3840x2160/4096x2160 (23.98p/24p/25p/29.97p/30p)

Note: Due to constant effort to improve products and product features, specifications may change without notice.

Rent your Lilliput BM280-12G here